



[Advanced Search](#) [Preferences](#) [Language Tools](#) [Search Tips](#)

Google SafeSearch is ON

"of" is a very common word and was not included in your search. [\[details\]](#)

"bus" (and any subsequent words) was ignored because we limit queries to 10 words.

[Web](#) [Images](#) [Groups](#) [Directory](#) [News](#)

Searched the web for **dma partial transfer period of time subset data items counter release bus with Safesearch**

Data Transfer

shopper.cnet.com

Find the best deal! Compare prices, Reviews and More - CNET Shopper.com

Sponsored

Link

www.mudcentral.com/sysops/sysnotes.txt

... a **DMA** server you will not be able to **transfer** your copy ... **OPTION ONE (PARTIAL RESET)**

If you wish to reset all ... WCCDMA.SYS file (for running on a **DMA** server) after ...

101k - [Cached](#) - [Similar pages](#)

[\[PDF\]](#) [Network Pump \(NP\) Security Target](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... of Contents Approved for public **release**; distribution unlimited ... as abnormally terminated

in a **data** structure that can be consulted the next **time** a connection ...

chacs.nrl.navy.mil/publications/ CHACS/2000/2000moore-NPST.pdf - [Similar pages](#)

[Cray T3E User's Guide](#)

... **Data transfer** through the memory is enhanced by use of the E ... Some **partial** planes are supported to increase the ... are used to speed-match the **DMA** transfers from ...

www.wes.hpc.mil/faq/hpcsug/t3e_bd.htm - 101k - [Cached](#) - [Similar pages](#)

[\[PDF\]](#) [VSI Alliance Deliverables Document Version 2.5.0](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... IPP OCB AMS I/V VER QTY VC **Transfer** System Level ... a more specific format or set of formats at a later **time**. ... 2.1.1 RTL Source Verilog/ VHDL Synthesis **Subset M CM** ...

www.vsi.org/library/specs/deliver011502.pdf - [Similar pages](#)

[\[PDF\]](#) [VSI Alliance Deliverables Document Version 2.6.0](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... OCB AMS I/V VER QTY VC **Transfer** System Level ... format or set of formats at a later **time**. ... 1: VSI Alliance Specification (AMS 1 2.2) **Data** Deliverables (Continued ...

www.vsi.org/library/deliver051402.pdf - [Similar pages](#)

[\[PDF\]](#) [User Guide](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... CD-ROM buffer Comms device Glossary GTE : Geometry **Transfer** Engine GPU : Graphics Processing Unit SPU : Sound Processing Unit MDEC : **Data** Decompression Engine ...

www.upl.cs.wisc.edu/~hamblin/files/usrguid.pdf - [Similar pages](#)

[\[PDF\]](#) [ADSP-21065L EZ-KIT Lite Evaluation System Manual, Version 2.0](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... EZ-KIT Lite hardware is warranted against defects in materials and workmanship for a **period** of one ... 27 3.3.3 Method 1: Using the Monitor's Codec **DMA** Buffers and ...

www.analog.com/Analog_Root/static/library/dspManuals/pdf/ADSP-21065L_EZ-KIT_Lite_Manual_Rev2.pdf - [Similar pages](#)

Sponsored Links

Large Data Transfer

Reliable Data Delivery Software

10x Faster than FTP

onionnetworks.com

Interest:

PC to PC Data Transfer

FastLynx lets you transfer files

quickly and easily - Try it Free!

www.FastLynxSoftware.com

Interest:

[See your message here...](#)

BEST AVAILABLE COPY

[PDF] DataGrid

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Specification Language SMTP Simple Mail **Transfer** Protocol SNMP ... but some were identified as **partial** interim solutions ... list, users, I/O port, **DMA** allocation, and ...

hep-proj-grid-fabric.web.cern.ch/hep-proj-grid-fabric/ Tools/DataGrid-04-TED-0101-3_0.pdf - [Similar pages](#)

www.vacets.org/diction/English/S_Engl.txt

... Scott domain An {algebraic}, {boundedly complete}, {complete **partial** order ... See also {**DMA**}. ... heads over the target track accurately enough to start **data transfer**. ...

101k - [Cached](#) - [Similar pages](#)

[PDF] OpenVMS VAX System Dump Analyzer Utility Manual

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... SDA-3 SDA-7 Comparison of Full and **Subset** Dump Files ... should have some knowledge of OpenVMS **data** structures to ... the status of each processor at the **time** of the ...

h71000.www7.hp.com/doc/73final/documentation/pdf/OVMS_73_VAX_SDA.pdf - [Similar pages](#)

◀ Goooooooooooooogle ▶

Result Page: [Previous](#) [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [11](#) [Next](#)

dma partial transfer period of time subset data items counter rel

Google Search

[Search within results](#)

[Google Home](#) - [Advertise with Us](#) - [Business Solutions](#) - [Services & Tools](#) - [Jobs, Press, & Help](#)

©2003 Google

BEST AVAILABLE COPY



[Advanced Search](#) [Preferences](#) [Language Tools](#) [Search Tips](#)

Google SafeSearch is ON

"of" is a very common word and was not included in your search. [\[details\]](#)

"bus" (and any subsequent words) was ignored because we limit queries to 10 words.

[Web](#) [Images](#) [Groups](#) [Directory](#) [News](#)

Searched the web for **dma partial transfer period of time subset data items counter release bus** with **Safesearch**

Data Transfer

[shopper.cnet.com](#)

Find the best deal! Compare prices, Reviews and More - CNET Shopper.com

Sponsored
Link

[\[PDF\]Maritime SIGINT Architecture Technical Standards Handbook](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... serving both the cryptologic **subset** of naval ... mandates standards for precision **time**

and navigation ... Chapter Six, "Information **Transfer** Services," mandates ...

[www.tscmplus.com/sigintarchmsh.pdf](#) - [Similar pages](#)

[\[PS\]plg.uwaterloo.ca/~ftp/uSystem/uC++book.ps.gz](#)

File Format: Adobe PostScript - [View as Text](#)

... statementsS4 endif In this example, all 3 if statements **transfer** to the ... some later **time**. ... In practice, an execution-state consists of the **data items** created by ...

[Similar pages](#)

[\[PDF\]IDT77201 NICStAR™](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... The SAR **DMA's** the reassembled cells to ... virtual start address of a free buffer) - **Partial** CRC value ... (8). The NICStAR performs a PCI Bus Master **transfer** of the ... [srv.icom4u.co.kr/datasheet/network/atm/idt/idt77201/IDT77201.pdf](#) - [Similar pages](#)

[[More results from srv.icom4u.co.kr](#)]

[\[PS\]www.mit.edu/afs/sipb/contrib/doc/specs/ic/cpu/sparc/v9.ps](#)

File Format: Adobe PostScript - [View as Text](#)

... 267 D.5 Specification of **Partial** Store Order (PSO ... re-architected the trap entry mechanism to **transfer** control into ... a great deal of time over a **period** of three ...

[Similar pages](#)

[[More results from www.mit.edu](#)]

[\[PS\]www.cise.ufl.edu/help/software/doc/XFree86/man/man.PS.gz](#)

File Format: Adobe PostScript - [View as Text](#)

... A **period** (.) is a tight binding and is used to ... the hierarchy to lowest), one component at a **time**. ... sources (other programs usually support some **subset** of these ...

[Similar pages](#)

[\[PS\]beige.ucs.indiana.edu/MPI/mpi2-report.ps](#)

File Format: Adobe PostScript - [View as Text](#)

... During the **period** of development of the Message Passing Interface ... Examples include the **data transfer** for an MPI IRECV ... are both compile-time and run-time ways to ...

[Similar pages](#)

[\[PS\]mirror.mcs.anl.gov/suse/i386/7.1/docu/pkg_english.ps.gz](#)

File Format: Adobe PostScript - [View as Text](#)

... simply setting it to yes will enable IDE **DMA** for all ... for the password for initializing an check **period** of a ... Rpmfind can also do the **transfer** once the list of ...

[Similar pages](#)

Sponsored Links

[Large Data Transfer](#)

Reliable Data Delivery Software
10x Faster than FTP
[onionnetworks.com](#)
Interest:

[PC to PC Data Transfer](#)

FastLynx lets you transfer files quickly and easily - Try it Free!
[www.FastLynxSoftware.com](#)
Interest:

[See your message here...](#)

BEST AVAILABLE COPY

[MSDN Home](#) > [MSDN Library](#) > [Kernel-Mode Driver Architecture](#) > [Design Guide](#) > [Input/Output Techniques](#)

Kernel-Mode Driver Architecture: Windows DDK

Splitting Transfer Requests

Any driver might need to split up a transfer request and carry out more than one DMA transfer operation to satisfy a given IRP, depending on the following:

- The number of map registers returned by **IoGetDmaAdapter**
- The bytes of data to be transferred, contained in the **Length** member of the driver's I/O stack location for the IRP
- The number of page boundaries, in system physical memory, for the buffer into which or from which the driver is to transfer data
- Device-specific constraints on the driver's DMA operations. For example, the system “AT” disk driver must split up transfer requests for more than 256 sectors due to the disk controller’s limitations.

A driver can determine the number of map registers needed to transfer all the data specified by an IRP as follows:

1. Call **MmGetMdlVirtualAddress**, passing a pointer to the MDL at **Irp->MdlAddress**, to get the starting virtual address for the buffer. Note that a driver *must not* attempt to access memory using this virtual address. The value returned by **MmGetMdlVirtualAddress** is an index into the MDL, not necessarily a valid address.
2. Pass the returned index and the value of **Length** in the driver's I/O stack location of the IRP to the ADDRESS_AND_SIZE_TO_SPAN_PAGES macro.

If the value returned by ADDRESS_AND_SIZE_TO_SPAN_PAGES is greater than the *NumberOfMapRegisters* value returned by **IoGetDmaAdapter**, the driver cannot transfer all requested data for this IRP in a single DMA operation. Instead, it must do the following:

1. Split the buffer into pieces that are sized to suit the number of available map registers (and any device-specific DMA constraints).
2. Carry out as many DMA operations as it takes to satisfy the transfer request.

For example, suppose ADDRESS_AND_SIZE_TO_SPAN_PAGES indicates that twelve map registers are needed to satisfy a transfer request, but the *NumberOfMapRegisters* value returned by **IoGetDmaAdapter** is only five. (Assume no device-specific DMA constraints.) In this case, the driver must carry out three DMA transfer operations, calling **MapTransfer** three times to transfer all the data requested by the IRP.

The system's DMA device drivers use various techniques to split up a DMA transfer when there are not enough map registers to satisfy an IRP with a single I/O operation. One technique to use is the following:

1. Call **IoAllocateMdl** to allocate an MDL describing a portion of the user buffer.

BEST AVAILABLE COPY

2. Call **MmProbeAndLockPages** to lock down that portion of the user buffer.
3. Transfer the data for that portion of the buffer.
4. Call **MmUnlockPages** and do either of the following:
 - If the MDL that the driver allocated in Step 1 is large enough for the next piece of the transfer, call **MmPrepareMdlForReuse** and repeat Steps 2 through 4.
 - Otherwise, call **IoFreeMdl** and repeat Steps 1 through 4.
5. Call **MmUnlockPages** and **IoFreeMdl** when all the data has been transferred.

If a highest-level driver cannot lock down the entire user buffer with **MmProbeAndLockPages** in a machine with limited memory, it can do the following:

1. Call **IoBuildSynchronousFsdRequest** to allocate a partial-transfer IRP and lock down a portion of the user buffer. The locked-down area is usually either a multiple of PAGE_SIZE or is sized to suit the underlying device's transfer capacity.
2. Call **IoCallDriver** for the partial-transfer IRP, and call **KeWaitForSingleObject** to wait on an event object that the driver set up to be associated with its partial-transfer IRP, if lower drivers return STATUS_PENDING.
3. When it regains control, repeat Steps 1 and 2 until all the data has been transferred, and, then, complete the original IRP.

When a storage class driver splits up large transfer requests for underlying SCSI port/miniport drivers, it allocates an additional IRP for each piece of the transfer request. It registers an **IoCompletion** routine for each driver-allocated IRP, to track the status of the full transfer request and to free the driver-allocated IRPs. Then it sends these IRPs on to the port driver using **IoCallDriver**.

Other class/port drivers can use this technique only if the class driver can determine how many map registers are available to the port driver. The port driver must store this configuration information in the registry for the paired class driver, or the paired drivers must define a private interface, using internal device I/O control requests, to pass configuration information about the number of available map registers from the port driver to the class driver.

A monolithic driver (that is, a driver not part of a class/port pair) for a DMA device must split up large transfer requests for itself. Such drivers usually split a large request into pieces and carry out a sequence of DMA operations in order to satisfy the IRP.

If a transfer request is too large for the underlying device driver to handle, a higher-level driver can call **MmGetMdlVirtualAddress** and **IoBuildPartialMdl**, then set up a sequence of partial-transfer IRPs for underlying device drivers.

[Send feedback on this topic.](#) / Built on Thursday, February 13, 2003

[Contact Us](#) | [E-Mail this Page](#) | [MSDN Flash Newsletter](#) | [Legal](#)

© 2003 Microsoft Corporation. All rights reserved. [Terms of Use](#) [Privacy Statement](#) [A](#)